



## Energebnis® LED Tunnelbeleuchtung



Artikelnummer	EN-TL370-001			EN-TL370-002		
Volt	85-265V AC			85-265V AC		
LED Cree/Edison	1x50W/70W/80W			1x50W/70W/80W		
Leistung	50W / 70W / 80W			50W / 70W / 80W		
Abstrahlwinkel	130° Grad			40° Grad		
Farbtemperaturen	CW / NW / WW / R / G / B			CW / NW / WW / R / G / B		
Lichtstrom / Lumen	<b>50W</b>	<b>70W</b>	<b>80W</b>	<b>50W</b>	<b>70W</b>	<b>80W</b>
	CW 4000lm	5600lm	6400lm	CW 4000lm	5600lm	6400lm
	NW 3750lm	5250lm	6000lm	NW 3750lm	5250lm	6000lm
	WW 3500lm	4900lm	5600lm	WW 3500lm	4900lm	5600lm
Schutzklasse	IP 65			IP65		
Lebensdauer	50.000 Stunden			50.000 Stunden		
Abmessungen (mm)	L393xB285xT93			L393xB285xT93		
Garantie	24 Monate			24 Monate		
Gewicht	7,5 Kg			7,5 Kg		



## Energiegebnis® LED Tunnelbeleuchtung



Artikelnummer	EN-TL570-001			EN-TL570-002		
Volt	85-265V AC			85-265V AC		
LED Cree/Edison Bridgelux	2 x 40W/50W/60W/70W			2 x 40W/50W/60W/70W		
Leistung	80W / 100W / 120W / 140W			80W / 100W / 120W / 140W		
Abstrahlwinkel	130° Grad			40° Grad		
Farbtemperaturen	CW / NW / WW / R / G / B			CW / NW / WW / R / G / B		
Lichtstrom / Lumen	<b>100W</b>	<b>120W</b>	<b>140W</b>	<b>50W</b>	<b>70W</b>	<b>80W</b>
	CW 8000lm	9600lm	11200lm	CW 8000lm	9600lm	11200lm
	NW 7500lm	9000lm	10500lm	NW 7500lm	9000lm	10500lm
	WW 7000lm	8400lm	9800lm	WW 7000lm	8400lm	9800lm
Schutzklasse	IP 65			IP65		
Lebensdauer	50.000 Stunden			50.000 Stunden		
Abmessungen (mm)	L593xB285xT93			L593xB285xT93		
Garantie	24 Monate			24 Monate		
Gewicht	11,2 Kg			11,2 Kg		